

## SEAL CLEAN KEYBOARD WITH SMART CARD READER

Model: SSKSV208Rxx

Seal Clean Waterproof Keyboards with a built-in tap-and-go RFID card reader from Seal Shield. Keyboards have a 100% waterproof & dishwasher-safe rating that is IPX8-certified and designed to withstand industrial-grade disinfectants & cleaners. True type keyboard with tactile feel and full travel keys for smooth and natural typing. Features a Quick Connect Cable with RF shielding and a Seal Cap™ for easy plug-and-play. Built-in Contact Card Reader for added security supports all major smart cards, network log-in and single sign-on. Laser-etched keys stand up to frequent and vigorous cleaning. ABS plastic with stainless steel screws.

### FEATURES:



100% Waterproof,  
Dishwasher-Safe,  
& Fully Submersible



Gold Coated USB  
Quick Connect Cable,  
RF Shielding, & Seal  
Cap™ Protector



Full-Size Numeric  
Keypad, Laser Etched  
Keycaps



Available in a Range  
of International Languages



Standard Style Keyboard  
for Smooth Typing



Designed to Withstand  
Industrial-Grade Disinfectants  
& Cleaners



Built-In Contact (CAC)  
Card Reader



ABS Plastic with  
Stainless Steel Screws  
& Non-Corrosive Components



SSKSV208Rxx

### ADVANCED CLEANING CAPABILITIES

- Dishwasher-Safe
- Compatible with Spray & Wipe Disinfectant Products:
  - Clorox Healthcare®
  - Lysol®
  - PDI Products
  - Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants



# SEAL CLEAN KEYBOARD WITH SMART CARD READER

Model: SSKSV208Rxx

## TECHNICAL DATA:

Compatibility:	Windows®
Construction:	ABS Plastic (Standard Style)
Key Layout:	104 US Language
Net Dimensions L x W x H:	18.07 x 6.85 x 1.38 in (45.9 x 17.4 x 3.5 cm)
Gross Dimensions L x W x H:	18.74 x 7.76 x 1.75 in (47.6 x 19.7 x 4.45 cm)
Net Weight:	2.02 lb (0.915 kg)
Gross Weight:	2.35 lb (1.065 kg)
Cable Length:	6 in (15cm) Quick Connect Cable with 6 ft Extension Cable
Connection Type:	Gold Plated USB (can support PS/2 technology)
Supported Smart Cards:	5V, 3V and 1.8V, ISO/IEC 7816 Class A/B/C
Card Size:	ID-1
Card Reader Speed:	12 Mbps (USB 2.0 full speed)
Card Reader Life Cycle:	100,000 Card Insertions
Key Switch Force:	53 ± 7 gf
Key Switch Life Cycle:	Greater than 10 Million Keystrokes
Key Switch Type:	Membrane Key Switch with Tactile Feedback
Keycaps Imaging Type:	Laser Etched
Operating Current:	60mA
Total Key Travel:	4.0 ± 0.2 mm
Operating Voltage:	5VDC
Storage Temperature:	-5° - 140° F (-20° to 60° C)
EMI - RFI:	Conforms to FCC Rules for Class B Device
Waterproof/Dustproof Ratings:	IPX8, NEMA 4X
Approvals/Certifications:	RoHS, WEEE, CE, FCC, WHQL, ICES-003, REACH, Cal Prop 65
Card Reader Compliance:	ISO/IEC 7816, USB CCID, PC/SC, EMV 2008, GSA FIPS 201



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners.

Limited 2-Year Warranty